



Purpose: ballistic protection for helicopter cabins, protecting basic controlling elements and the crew; plates protecting special-purpose transport against regular and armour-piercing missiles AP type, cal. 5.56 mm and 7.62 mm.

Technical data

Type of missile	Type of ceramic	Thickness [mm]	Weight [kg]
7,62 mm AP V = 695 ±10 m/s, m = 79 g; poziom 2 wg STANAG 4569	Al ₂ O ₃	~ 14	~ 34
	SiC	~ 14	~ 29
	B4C	~ 14	~ 25
7,62 B-32 V = 850 ±10 m/s, m = 9,95 g; poziom 3 wg STANAG 4569	Al ₂ O ₃	~ 19	~ 44
	SiC	~ 19	~ 38
	B4C	~ 19	~ 33
12,7 B-32 V = 817,5 m/s m = 48,2 g;	Al ₂ O ₃	~ 31	~ 73
	SiC	~ 30	~ 65
	B4C	~ 29	~ 70

This document is the property of Lubawa SA Ostrów Wielkopolski. It is protected by the copyright and may not be reproduced or used in any manner whatsoever without the express written permission of the owner.

LUBAWA S.A. Staroprzygodzka 117, 63-400 Ostrów Wielkopolski

+48 607 140 930
+48 56 699 4009

+48 62 737 5708

www.lubawa.com.pl

export@lubawa.com.pl

