



The NPSO-30 tent is mainly designed for decontamination purposes, but it may also be used as command post, sleeping quarters, medical tent, etc. The dome is made with two-side rubber coating technology, and the structure of the tent is adapted for modular connection. Each tent has two identical end walls, equipped by standard with a central entrance door closed with zippers. The entrance doors can be rolled up and fold with bands with buckles. The entrances are framed with a flange for immediate connection with an identical flange from another tent, creating a row of tents. There are four large and four small sleeves for connecting heater or air conditioner conduits and cables. The dome is glued to the floor and the pneumatic frame.

The frame also has glued-in holders for fixing lights and other equipment inside the tent. The tent has a net fixed to the ceiling for hanging medical instruments or other equipment. The tent can be further equipped with curtains, partition walls, and decontamination lines, depending on its purpose. The tent is equipped with an external metal frame used as additional reinforcement for the pneumatic structure in case of pressure drop or damage to one of the inflatable inner tubes during warfare. The fixed frame can be deployed on the ground without the need for use of any additional equipment. Pulling the dome over the fixed frame can be performed from the ground level with a system of lines and blocks.

Technical parameters

Dimensions (without the fixed frame)	6 x 5,04 x 3,3 [m]
Dimensions (with the fixed frame)	6,5 x 6,04 x 3,5 [m]
Weight	105 kg – external metal frame 115 kg tent (dome, floor, pneumatic frame)
Includes	transport cover, repair kit, anchoring equipment
Valves	inlet-outlet valve for pumping with a compressor or pump, Z-50 valve for pumping from a compressed air tank, safety valve

This document is the property of Lubawa SA Ostrów Wielkopolski. It is protected by the copyright and may not be reproduced or used in any manner whatsoever without the express written permission of the owner.

LUBAWA S.A. Staroprzygodzka 117, 63-400 Ostrów Wielkopolski

+48 607 140 930
+48 56 699 4009

+48 62 737 5708

www.lubawa.com.pl

export@lubawa.com.pl

