



The **WS Rigid Frame Base (NS-26)** is a complete logistic set, intended for the accommodation of users in field conditions and their isolation from the influence of adverse external factors, including: weather conditions and the activity of invertebrates (insects) and vertebrates (amphibians, reptiles, birds and mammals), which might be dangerous to human health and life. The base and its tents is a very universal product. It meets the requirements for accommodation of 6 people with the equipment (one tent).

The NS-26 tent is suitable for all terrain conditions (mountains, uplands, lowlands, deserts, forests and lakes, etc.) and climatic zones (polar, moderate and inter-tropical), including conditions of high air and ground humidity, intensive sunlight, as well as low temperatures, intensive rain and snow. The operating temperature range is from -30°C to $+60^{\circ}\text{C}$. Inside the tent there is a possibility of maintaining comfortable temperature from $+18^{\circ}\text{C}$ to $+21^{\circ}\text{C}$, regardless of climatic zones, thanks to the use of additional equipment, e.g. air conditioners, heaters, power generators.

NS-26 TENT FEATURES:

- The frame is made of unified aluminum profiles with a design that allows for quick disassembly.
- The canopy is made of a unique fabric with an elastomeric coating providing masking properties in near infrared and thermal and light reflexes inside the tent.
- Two entrances are available.
- An additional door secured with a mosquito net may be used for ventilating the tent.
- 4 windows with a 3-layer design.
- The floor is integrated with the canopy of the tent to ensure tightness.
- The inner lining improves thermal comfort.
- 4 technical sleeves for connecting the heater / air conditioner.
- 4 ventilation openings reduce condensation of vapor.
- External heat shields are used to improve thermal comfort and mask the tent.
- The tents can be joined together in series or in series and parallel, with the use of a universal joint tent.





WS RIGID FRAME BASE (NS-26)

Technical parameters*	
Length	5,00 m (±0,50 m)
Width	5,50 m (±0,50 m)
Crest height	2,60 m (±0,20 m)
Usable floor space	25 m ² (±3 m ²)
Total weight (canopy + frame)	max. 200 kg

* The technical parameters provide borderline values for the frame of a single NS-26 tent.

BASE CONFIGURATION:

1. Frame tent – 4 pcs.
2. Joint tent – 1 piece
3. Summer camo heat shield for joint tent – 1 piece
4. Forest camo heat shield for joint tent – 1 piece
5. Winter camo heat shield for joint tent – 1 piece
6. Desert camo heat shield for joint tent – 1 piece
7. Main heat shield NS-26 – 4 pcs.
8. Forest camo heat shield – 4 pcs.
9. Winter camo heat shield – 4 pcs.
10. Desert camo heat shield – 4 pcs.
11. Folding camp bed – 24 pcs.
12. Camp bed mosquito net – 24 pcs.
13. Tent air conditioner – 4 pcs.
14. Mobile heater – 4 pcs.
15. Power generator – 4 pcs.
16. Tent lamp IP44 – 8 pcs.
17. Wireless tent lamp – 16 pcs.
18. Extension cord drum – 8 pcs.
19. Engineering set – 2 pcs.
20. 20-foot dedicated container – 1 piece.

This document is the property of Lubawa SA Ostrów Wielkopolski. It is protected by the copyright and may not be reproduced or used in any manner whatsoever without the express written permission of the owner.