

## NTD-1 FABRIC

<b>Index</b>	55005EURO1 -0759
<b>Fabric</b>	Glass fabric 205±15 g/m <sup>2</sup> , white
<b>Coating</b>	Two-side CR; 110 g/m <sup>2</sup> for each side, flame retardant, unvulcanized
<b>Available colors</b>	Black
<b>Spacer</b>	Embossed LDPE foil

Parameters	Unit	Value	Test methods
Useful width	cm	≥ 124	PN-EN ISO 2286-1
Weight	g/m <sup>2</sup>	425±30	PN-EN ISO 2286-2

### Storage conditions

Unvulcanized coated fabric should be stored in dry rooms, in conditions that protect against getting wet, dirty, mechanical and chemical damage. The storage temperature should be between +10 and +30°C. Away from sources of heat, direct UV radiation and ionizing radiation that generates ozone (e.g. operating electric engines). Unvulcanized fabrics should be stored unstressed, wound on a roller and wrapped in stretch foil. The rollers can be stacked in a maximum of 3 layers. The maximum shelf life of the product is 90 days from the production date.

### Customer service (7:00-15:00)

COORDINATOR  
ANNA KOSEDA  
**Department of sales of fabrics,  
rubbers, rescue and safety  
equipment**  
Tel.: + 48 603 201 773  
akoseda@lubawa.com.pl

COORDINATOR  
PAULINA WICHROWSKA  
**Specialty sales department**  
Tel: +48 566 994 008  
pwichrowska@lubawa.com.pl

EXPORT MANAGER  
JOANNA PIECHOCKA  
**Export sales department**  
mobile: +48 607 140 930  
jpiechocka@lubawa.com.pl

Dokumentacja jest własnością firmy Lubawa SA Ostrów Wielkopolski. Podlega ochronie prawnej wynikającej z prawa autorskiego. Wszelkie wykorzystywanie bez pisemnej zgody właściciela jest niedozwolone.

