

NTD-18 FABRIC

Index	55005EURO18-0283
Fabric	PES fabric HT1100DTEX, 234±15 g/m ² , white color
Coating	Two-side 150 g/m ² yellow vulcanized CSM on one side 80 g/m ² black vulcanized CR on the other side
Available colors	Yellow/Black
Spacer	Embossed LDPE foil

Parameters	Unit	Value	Test methods
Useful width	cm	≥ 150	PN-EN ISO 2286-1
weight	g/m ²	464±30	PN-EN ISO 2286-2

Storage conditions

Coated vulcanized fabric should be stored in dry rooms, in conditions that protect against getting wet, dirty, mechanical and chemical damage. The storage temperature should be from -10 to +50°C. Away from direct sources of heat, UV radiation and ionizing radiation that generates ozone (e.g. operating electric motors). Fabrics should be stored taut, wound on a roller and protected with stretch foil. The rollers can be stacked with a maximum of 4 layers. The maximum shelf life of the product is 3 years from the date of production.

Customer service (7:00-15:00)

COORDINATOR
ANNA KOSEDA

**Department of sales of fabrics,
rubbers, rescue and safety
equipment**

Tel.: + 48 603 201 773
akoseda@lubawa.com.pl

COORDINATOR
PAULINA WICHROWSKA

Specialty sales department

Tel: +48 566 994 008
pwichrowska@lubawa.com.pl

EXPORT MANAGER
JOANNA PIECHOCKA

Export sales department

mobile: +48 607 140 930
jpiechocka@lubawa.com.pl

Dokumentacja jest własnością firmy Lubawa SA Ostrów Wielkopolski. Podlega ochronie prawnej wynikającej z prawa autorskiego. Wszelkie wykorzystywanie bez pisemnej zgody właściciela jest niedozwolone.

