

NTD-4 FABRIC

Index	55005EURO4 -0759
Fabric	Glass fabric, 205±15 g/m ² , white color
Coating	Two-side CR 110 g/m ² for each side, unvulcanized
Available colors	Black
Spacer	Embossed LDPE foil

Parameters	Unit	Value	Test methods
Useful width	cm	≥ 124	PN-EN ISO 2286-1
Weight	g/m ²	425±30	PN-EN ISO 2286-2

Storage conditions

Unvulcanized coated fabric should be stored in dry rooms, in conditions that protect against getting wet, dirty, mechanical and chemical damage. The storage temperature should be between +10 and +30°C. Away from sources of heat, direct UV radiation and ionizing radiation that generates ozone (e.g. operating electric engines). Unvulcanized fabrics should be stored unstressed, wound on a roller and wrapped in stretch foil. The rollers can be stacked in a maximum of 3 layers. The maximum shelf life of the product is 90 days from the production date.

Customer service (7:00-15:00)

COORDINATOR
ANNA KOSEDA
**Department of sales of fabrics,
rubbers, rescue and safety
equipment**
Tel.: + 48 603 201 773
akoseda@lubawa.com.pl

COORDINATOR
PAULINA WICHROWSKA
Specialty sales department
Tel: +48 566 994 008
pwichrowska@lubawa.com.pl

EXPORT MANAGER
JOANNA PIECHOCKA
Export sales department
mobile: +48 607 140 930
jpiechocka@lubawa.com.pl

Dokumentacja jest własnością firmy Lubawa SA Ostrów Wielkopolski. Podlega ochronie prawnej wynikającej z prawa autorskiego. Wszelkie wykorzystywanie bez pisemnej zgody właściciela jest niedozwolone.

