

NTK-5 FABRIC

Index	55005PRIM05-2924
Fabric	Glass fabric 205±15 g/m ²
Coating	Two-side MVQ 155 g/m ² on one side- unvulcanized, 100 g/m ² on the other side- unvulcanized Both sides- flame retardant
Available colors	red
Spacer	Embossed LDPE foil

Parameters	Unit	Value	Test methods
Useful width	cm	≥ 124	PN-EN ISO 2286-1
Weight	g/m ²	460±20	PN-EN ISO 2286-2

Storage conditions

Unvulcanized coated fabric should be stored in dry rooms, in conditions that protect against getting wet, dirty, mechanical and chemical damage. The storage temperature should be between +10 and +30°C. Away from sources of heat, direct UV radiation and ionizing radiation that generates ozone (e.g. operating electric engines). Unvulcanized fabrics should be stored unstressed, wound on a roller and wrapped in stretch foil. The rollers can be stacked in a maximum of 3 layers. The maximum shelf life of the product is 60 days from the production date.

Customer service (7:00-15:00)

COORDINATOR
ANNA KOSEDA

**Department of sales of fabrics,
rubbers, rescue and safety
equipment**

Tel.: + 48 603 201 773
akoseda@lubawa.com.pl

COORDINATOR
PAULINA WICHROWSKA

Specialty sales department

Tel: +48 566 994 008
pwichrowska@lubawa.com.pl


EXPORT MANAGER
JOANNA PIECHOCKA


Export sales department

mobile: +48 607 140 930
jpiechocka@lubawa.com.pl

Dokumentacja jest własnością firmy Lubawa SA Ostrów Wielkopolski. Podlega ochronie prawnej wynikającej z prawa autorskiego. Wszelkie wykorzystywanie bez pisemnej zgody właściciela jest niedozwolone.

LUBAWA S.A. ul. Staroprzygodzka 117, 63-400 Ostrów Wielkopolski

 +48 62 737 5777

 +48 62 737 5708

 www.lubawa.com.pl

 info@lubawa.com.pl

