

CONDUCTIVE BLACK TAPE NTU-52

| | |
|--------------------------|--|
| Index | 55005NTU520-0759 |
| Fabric | Polyester 55 g/m ² |
| Coating | Two-side, SBR 20-30 g/m ² , vulcanized |
| Available colours | Black |

| Physical parameters | Unit | Value | Test standard |
|---------------------|------------------|---------|-----------------------------|
| Resistivity | Ω x cm | < 130 | Internal Procedure/LUBAWA/1 |
| Weight | g/m ² | 75 ± 10 | PN-EN ISO 2286-2 |
| Thickness | mm | ≤ 0,13 | PN-EN ISO 2286-3 |

possibility of cutting to a width of 20 mm

Storage conditions

Coated vulcanized fabric should be stored in dry rooms, in conditions that protect against getting wet, dirty, mechanical and chemical damage. The storage temperature should be from -10 to +50°C. Away from direct sources of heat, UV radiation and ionizing radiation that generates ozone (e.g. operating electric motors). Fabrics should be stored taut, wound on a roller and protected with stretch foil. The rollers can be stacked with a maximum of 4 layers. The maximum shelf life of the product is 3 years from the date of production.

Customer service (7:00-15:00)

COORDINATOR
ANNA KOSEDA
**Department of sales of fabrics,
rubbers, rescue and safety
equipment**
Tel.: + 48 603 201 773
akoseda@lubawa.com.pl

COORDINATOR
PAULINA WICHROWSKA
Specialty sales department
Tel: +48 566 994 008
pwichrowska@lubawa.com.pl

EXPORT MENAGER
JOANNA PIECHOCKA
Export sales department
mobile: +48 607 140 930
jpiechocka@lubawa.com.pl

Dokumentacja jest własnością firmy Lubawa SA Ostrów Wielkopolski. Podlega ochronie prawnej wynikającej z prawa autorskiego. Wszelkie wykorzystywanie bez pisemnej zgody właściciela jest niedozwolone.

