

TECHNICAL SPECIFICATION



Index 55005SNO-1 -0410

Fabric Cotton 100%, 120g/m2

Coating One-side NR;

100-160 g/m², unvulcanized

Available colours Black, natural

Parameters	Unit	Value	Test methods
Useful width *	cm	≥ 140	PN-EN ISO 2286-1
Weight	g/m²	250±30	PN-EN ISO 2286-2

^{*} possibility of cutting to a width of 20 mm

Storage conditions

Unvulcanized coated fabric should be stored in dry rooms, in conditions that protect against getting wet, dirty, mechanical and chemical damage. The storage temperature should be between +10 and +30°C. Away from sources of heat, direct UV radiation and ionizing radiation that generates ozone (e.g. operating electric engines). Unvulcanized fabrics should be stored unstressed, wound on a roller and wrapped in stretch foil. The rollers can be stacked in a maximum of 3 layers. The maximum shelf life of the product is 90 days from the production date.

Customer service (7:00-15:00)

COORDINATOR PAULINA WICHROWSKA

Specialty sales department

EXPORT MENAGER JOANNA PIECHOCKA

Export sales department

Tel: +48 566 994 008 pwichrowska@lubawa.com.pl mobile: +48 607 140 930 jpiechocka@lubawa.com.pl

Dokumentacja jest własnością firmy Lubawa SA Ostrów Wielkopolski. Podlega ochronie prawnej wynikającej z prawa autorskiego. Wszelkie wykorzystywanie bez pisemnej zgody właściciela jest niedozwolone

LUBAWA S.A. ul. Staroprzygodzka 117, 63-400 Ostrów Wielkopolski









































Department of sales of fabrics,

rubbers, rescue and safety

akoseda@lubawa.com.pl

COORDINATOR

ANNA KOSEDA

equipment Tel.: + +48 603 201 773